


CONSTRUCTION DRG No.

## P150/75




### TYPICAL EDGE/CROSS SECTION

#### SUPERIMPOSED LOADING

5KN/M<sup>2</sup> – 1.820M Max. CLEAR SPAN  
10KN/M<sup>2</sup> – 1.320M Max. CLEAR SPAN  
20KN/M<sup>2</sup> – 0.940M Max. CLEAR SPAN

#### CONCENTRATED LOADING

75KN ULTIMATE – N/A  
SELF WEIGHT = 132kgs/M<sup>2</sup>



LENS PATTERN  
(SCALE=1:5.)

FOR DIMENSIONS 'a', 'b', 'c' and 'd' PLEASE REFER TO THE RELEVANT DESIGN CRITERIA DETAIL  
SHEET Nos. PL-SPAN1 to 9 inc.

# luxcrete

LIMITED

Unit 2 Firbank Industrial Estate T:01582 488767  
Dallow Road Luton F:01582 724607  
Bedfordshire www.luxcrete.co.uk  
LU1 1TW E:enquiries@luxcrete.co.uk

LUXCRETE OPERATE A POLICY OF CONTINUAL IMPROVEMENT OF THEIR PRODUCTS. SPECIFICATIONS AND DETAILS ARE THEREFORE SUBJECT TO CHANGE WITHOUT NOTICE. ALL TECHNICAL INFORMATION CONTAINED WITHIN THIS DETAIL SHEET IS FOR GUIDANCE ONLY AND MAY BE INAPPROPRIATE UNDER PARTICULAR CONDITIONS.

© 2011 COPYRIGHT LUXCRETE LTD